

UTILITY
PATENT APPLICATION
TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

35.C14095

First Named Inventor or Application Identifier

TSUNEHIRO TSUKADA

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☐ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)

2. ☒ Specification Total Pages

3. ☒ Drawing(s) (35 USC 113) Total Sheets

4. ☒ Oath or Declaration Total Pages

- a. ☐ Newly executed (original or copy)
b. ☒ Unexecuted for information purposes
c. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]

i. ☐ **DELETION OF INVENTOR(S)**
Signed Statement attached deleting
inventor(s) named in the prior application, see
37 CFR 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference (useable if Box 4c is checked)
The entire disclosure of the prior application, from which a copy of
the oath or declaration is supplied under Box 4c, is considered as
being part of the disclosure of the accompanying application and is
hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)

7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)

- a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☐ Small Entity ☐ Statement filed in prior application
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____

18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label

05514

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

NAME

Address

City

State

Zip Code

Country

Telephone

Fax



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	10-20 =	0	X \$ 18.00 =	\$0
	INDEPENDENT CLAIMS (37 cfr 1.16(b))	6-3 =	3	X \$ 78.00 =	\$234.00
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$260.00 =	\$0
				BASIC FEE (37 CFR 1.16(a))	\$760.00
	Total of above Calculations =				\$994.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				0
	TOTAL =				\$994.00

19. Small entity status

- a. ☐ A Small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.


20. ☒ A check in the amount of \$ 994.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ _____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

NAME	LEONARD P. DIANA, ESQ.
SIGNATURE	
DATE	December 6, 1999

NAVIGATION APPARATUS CAPABLE OF GENERATING
AND DISPLAYING INFORMATION AND METHOD THEREFOR

BACKGROUND OF THE INVENTION

5 Field of the Invention

The present invention relates to a navigation apparatus capable of information display and a method therefor.

Related Background Art

10 In the conventional navigation apparatus, in case of dynamically generating and displaying a page or executing a time-consuming process in the server, there is often encountered a situation where a long time is required for generating data of which loading is
15 requested to the server, so that the loading operation cannot be conducted immediately. In such case, the process is conventionally continued either by awaiting the completion of the process or by the following method (1) or (2) or the combination thereof:

20 (1) executing the loading operation again manually. The user requests the loading again, then there is confirmed whether the data generation has been completed in response to the request, and, if completed, the data loading is started:

25 (2) executing inspection periodically.

Confirmation whether the data generation has been completed is made periodically, for example at an

662021 2659460

interval of 1 to 60 seconds, and, if completed, the data loading is started.

However, such conventional method (1) is associated with a drawback that, if the loading operation is requested before the completion of data generation, the loading operation cannot be executed as the process is interrupted for example by a time-out.

Also the conventional method (2) is associated with a drawback of increasing the load of the server receiving the communication or of the data communication channel such as a network.

The conventional method (2) is further associated with another drawback that will be explained with reference to Figs. 6A and 6B.

Fig. 6A shows a configuration of periodically issuing requests for data loading at a short interval, wherein 611, 612 and 613 indicate requests for data loading. If the requests for data loading are issued at such short interval, requests such as 611, 612 are issued uselessly before the data preparation is completed.

Fig. 6B shows a configuration of periodically issuing requests for data loading at a long interval, wherein 620 indicates a request for data loading. If the requests for data are issued at such long interval, an idle time 621 is generated from the data generation to the issuance of the request 620 for data loading,

whereby the data loading is delayed.

SUMMARY OF THE INVENTION

5 In consideration of the foregoing, an object of
the present invention is to provide an efficient
information display apparatus capable, in case of
loading the data generated in a server, of loading the
data promptly after the generation thereof without
wasteful request for data loading, and a method
10 therefor.

Another object of the present invention is to
provide an information display apparatus capable of
reducing the load in the server or in the data
communication channel in case of loading the data
15 generated in the server, and a method therefor.

According to one aspect, the present invention
which achieves these objectives relates to a data
processing method comprising a reception step of
receiving a request for data loading from a terminal,
20 an end discrimination step of discriminating whether
the generation of requested data is ended, a first
transmission step adapted, if the generation of the
requested data is ended, to transmit such data, an
estimation step adapted, if the generation of the
25 requested data is not ended, to estimate the end time,
and a second transmission step of transmitting the
estimated end time together with display information

09456997 120799

indicating that the data generation is in progress.

According to another aspect, the present invention which achieves these objectives relates to a data processing method comprising an issuing step of issuing
5 a request for data loading to a server, a display step of displaying display data received in response to the request, and a re-issuing step adapted, in case the estimated end time of data generation is received together with the display data, to re-issue the request
10 for data loading when such end time is reached.

According to yet another aspect, the present invention which achieves these objectives relates to a data processing apparatus comprising reception means for receiving a request for data loading from a
15 terminal, end discrimination means for discriminating whether the generation of the requested data is ended, first transmission means adapted, if the generation of the requested data is ended, to transmit such data, estimation means for estimating an end time if the
20 generation of the requested data is not ended, and second transmission means for transmitting the estimated end time together with display information indicating that the data generation is in progress.

According to still another aspect, the present
25 invention which achieves these objectives relates to a data processing apparatus comprising issuing means for issuing a request for data loading to a server, display

09456997.120799

means for displaying display data received in response to the request, and control means adapted, in case an estimated end time for data generation is received together with the display data, to so control said
5 issuing means as to issue again the request for data loading when said end time is reached.

According to still another aspect, the present invention which achieves these objectives relates to a computer readable storage medium storing a data
10 processing program for controlling a computer perform data processing, the program comprising codes for causing the computer to perform a reception step of receiving a request for data loading from a terminal, an end discrimination step of discriminating whether
15 the generation of requested data is ended, a first transmission step adapted, if the generation of the requested data is ended, to transmit such data, an estimation step adapted, if the generation of the requested data is not ended, to estimate the end time,
20 and a second transmission step of transmitting the estimated end time together with display information indicating that the data generation is in progress.

According to still another aspect, the present invention which achieves these objectives relates to a
25 computer readable storage medium storing a data processing program for controlling a computer perform data processing, the program comprising codes for

00456997 120799

causing the computer to perform an issuing step of
issuing a request for data loading to a server, a
display step of displaying display data received in
response to the request, and a re-issuing step adapted,
5 in case the estimated end time of data generation is
received together with the display data, to re-issue
the request for data loading when such end time is
reached.

Other objectives and advantages besides those
10 discussed above shall be apparent to those skilled in
the art from the description of a preferred embodiment
of the invention which follows. In the description,
reference is made to accompanying drawings, which form
a part thereof, and which illustrate an example of the
15 invention. Such example, however, is not exhaustive of
the various embodiments of the invention, and therefore
reference is made to the claims which following the
description for determining the scope of the invention.

20 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing the
configuration of a navigation system relating to a
first embodiment;

Fig. 2 is a flow chart showing the operation
25 sequence of a server;

Fig. 3 is a view showing the content of display of
received data in an information processing terminal;

004569 120799 652021 655460

Fig. 4 is a flow chart showing the operation sequence for obtaining an estimated process end time;

Fig. 5 is a view showing the content of memory for obtaining the estimated process end time;

5 Figs. 6A and 6B are views showing a conventional periodic data loading request;

Fig. 7 is a view showing the content of display of the information processing terminal in a second embodiment;

10 Fig. 8 is a block diagram showing the hardware configuration of the information processing terminal; and

Fig. 9 is a flow chart showing the operation sequence of the information processing terminal.

15

DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following there will be explained in detail a preferred embodiment of the present invention, with reference to the attached drawings.

20 [First embodiment]

Fig. 1 is a block diagram showing the configuration of a navigation system constituting a first embodiment of the present invention, wherein an information processing terminal 101 is composed for example of a personal computer and is connected with a server 103 through a data transfer path 102. A data storage device 105 is composed for example of a hard

25

094599 120799 662021 665460

disk, and is connected with the server 103 through a data transfer path 104.

Fig. 8 is a block diagram showing the configuration of the information processing terminal 101.

In Fig. 8, an input unit 801 is composed of a keyboard or a pointing device, and is used by the user for entering data and commands. An external memory unit 802 is composed of a memory device utilizing for example a hard disk as the memory medium, and is used for storing data loaded from the server 103. A display unit 803 is composed for example of a CRT or a liquid crystal display device, and is used for displaying a page generated in the server 103 or the result of processing.

A CPU 804 controls various units of the apparatus and reads and executes a program, thereby realizing various processes. A ROM 805 is used for storing fixed data and programs. A control program for realizing a process sequence, to be explained later with reference to a flow chart shown in Fig. 9, may be stored in the ROM 805 or read from the external memory unit 802. A RAM 806 provides a work area required for the processing of the present apparatus. A communication I/F 807, which is an interface for communication, is connected with the data transfer path 102. A bus 808 connects various units.

The server 103 also has a hardware configuration similar to that of the information processing terminal 101, and a control program for realizing the process sequence to be explained later with reference to flow charts in Figs. 2 and 4 is stored in a ROM or an external memory unit.

The user or a program on the information processing terminal 101 issues a request for data loading from the information processing terminal 101 to the server 103 through the data transfer path 102. In response to the request, the server 103 prepares the requested data and stores the data in the data storage device 105.

The present embodiment is featured by a fact that the data loading is not postponed until the completion of data preparation, but a display page is returned to the information processing terminal 101 according to the data generation time.

In case the process time is shorter than a predetermined time, the display page is immediately returned to the information processing terminal 101, but, in case the process time is longer than the predetermined time, a page including information for automatically requesting the data loading again at the estimated process end time is returned to the information processing terminal 101.

In either case, the information processing

09456597 120799
052021 2659460

terminal 101 can obtain, from the server 103, the display page itself or information indicating that the process requires time, at a time within the predetermined time.

5 The function of the server 103 of the above-described configuration will be explained with reference to a flow chart shown in Fig. 2.

At first a step S201 waits until the request for data loading is acquired from the information
10 processing terminal 101. When the request is acquired, a step S202 checks the data storage device 105 to discriminate whether the generation of the requested data has ended. If ended, a step S203 reads the
15 desired data from the data storage device 105 and transmits the data to the information processing
terminal 101 through the data transfer path 102, whereupon the process is terminated.

On the other hand, if the step S202 identifies that the generation of the requested data has not
20 ended, a step S204 estimates the time to the end of data generation by calculation, and generates a display page in which the estimated time is added. Then a step
S205 transmits the generated display page to the information processing terminal 101 through the data
25 transfer path 102, whereupon the process is terminated.

In the following the function of the information processing terminal 101 will be explained with

reference to a flow chart shown in Fig. 9.

At first a step S901 issues a request for data loading to the server 103. A step S902 displays the page received from the server 103 in response to the request, on the display unit 803. If a step S903 receives, together with the display page, re-loading information for automatically requesting the data loading again at the estimated process end time, the sequence proceeds to a step S904. If such information is not received, the process is terminated as the desired page has been received. A step S904 waits until the estimated end time, and, when such end time is reached, the sequence returns to the step S901 to request the data loading again.

Fig. 3 is a view showing the content of display of the received data in the information processing terminal 101 of the present embodiment. A page 301 is the display frame in case the processing does not take time in a system executing request for data processing or data loading by hyperlink. On the other hand, a page 302 is the display frame in case the processing takes time. The page 302 automatically request data loading immediately after the estimated process end time. If the generation of the requested data has ended at the transmission of the second request to the server 103, the page 301 is displayed.

In the following there will be explained, with

reference to a flow chart in Fig. 4 and Fig. 5 showing the memory area of the data storage device 105, the calculation procedure for the estimated process end time of data generation executed on the server 103.

5 Referring to Fig. 4, a step S401 stores the "generation start time" in an area 502, within an area 501 shown in Fig. 5. A next step S402 stores the "final size approximate estimate data" in an area 503 within the area 501. For example, in case of image
10 data, the final size can be calculated by "width × height × bit depth" of the image.

As an example of approximately estimating the time to the completion from a given time, there can be shown the following arithmetic calculation, utilizing the
15 values stored in the areas 502, 503 and the size of the data prepared up to the current time:

"estimate of final size" × ("current time" - "generation start time") ÷ "size generated up to a given time" = "time to completion at the given time",

20 estimated end time = "current time" + "time to completion at the given time".

The present embodiment is featured by a fact that the time obtained as explained above is set in the page 302 shown in Fig. 3, as the time for next request for
25 data loading.

The information processing terminal 101 displays the page 302, shown in Fig. 3, on the image display

004599 120760 652027 2655460

device, and the user may leave the display to automatically execute request for data loading again, or may execute another request by canceling the data loading.

5 As explained in the foregoing, the present embodiment estimates the end time of data generation and executes request for data loading at the estimated end time, so that there will not result the wasted request for data loading or the wasted waiting time explained in relation to Figs. 6A and 7B.

[Second embodiment]

10 In the following there will be explained a second embodiment of the present invention with reference to Fig. 7. As the basic configuration of the navigation apparatus of the present embodiment is same as that of the first embodiment shown in Fig. 1, reference is to be made to Fig. 1 as regards the configuration of the present embodiment.

15 The present embodiment is applied to the display of result in case the server executes a time-consuming process such as printing, fax transmission or mail transmission.

20 The information processing terminal 101 can continue another process without waiting for the completion of the transmitted request.

25 Fig. 7 shows the content of display in the information processing terminal 101 of the present

094599 120799 652021 2669460

embodiment. In case the process in the server does not take a long time, a page 701 indicating the result of process is displayed on the display unit 803 of the information processing terminal 101. On the other

5 hand, in case the process in the server takes a long time, the time to the end of process is approximately estimated and a page 702 indicating that the process is in progress is displayed on the display unit 803 of the information processing terminal 101. The page 702 sets
10 the end time of the process based on the estimated time, the display of the page indicating the result is requested at thus set time.

In case the result is available in response to the repeated request, the result is displayed by the page
15 701 on the display unit 803 of the information processing terminal 101. In case the result is not available, the server again estimates the time to the end of process, and display the page 702 on the image display device of the information processing terminal
20 101.

In the above-described navigation apparatus of the present embodiment, process can be executed effectively without the wasteful waiting time or wasteful request for data loading in the information processing
25 terminal, particularly in case a page is dynamically generated and displayed in the image display device of the information processing terminal or in case of

554021 659460

executing a time-consuming process in the server.

The present invention may be applied to a system consisting of plural equipment (for example host computer, interface devices, display device, etc.) or
5 an apparatus consisting of a single equipment, within an extent that the functions of the foregoing embodiments can be realized.

Also the present invention includes a case where the program codes of a software realizing the functions
10 of the aforementioned embodiments are supplied to a computer of a system or an apparatus connected to various devices in order to operate the devices so as to realize the functions of the aforementioned
15 embodiments and the functions of the aforementioned embodiments are realized by operating the devices by the computer (CPU or MPU) of the above-mentioned system or apparatus according to the program codes. In such
20 case the program codes themselves of the software realize the functions of the aforementioned embodiments, and the program codes themselves and the means for supplying the computer with such program codes, for example a memory medium storing the program codes, constitutes the present invention.

The memory medium storing such program codes can
25 be, for example, a floppy disk, a hard disk, an optical disk, a magnetooptical disk, a CD-ROM, a CD-R, a magnetic tape, a non-volatile memory card or a ROM.

0945597 120799

The present invention also includes such program codes not only a case where the functions of the aforementioned embodiments are realized by the execution of the read program codes by the computer but also a case where an operating system or the like functioning on the computer executes all or a part of the actual processes under the control of such program codes thereby realizing the functions of the aforementioned embodiments.

The present invention further includes a case wherein the program codes read from the memory medium are once stored in a memory provided in a function expansion board inserted into the computer or a function expansion unit connected to the computer, and a CPU provided in the function expansion board or the function expansion unit executes all the process or a part thereof according to the instructions of such program codes, thereby realizing the functions of the aforementioned embodiments.

In case the present invention is applied to the above-described memory medium, program codes corresponding to the aforementioned flow charts may be stored in such memory medium.

Although the present invention has been described in its preferred form with a certain degree of particularity, many apparently widely different embodiments of the invention can be made without

departing from the spirit and the scope thereof. It is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the appended claims.

09455997 120759

WHAT IS CLAIMED IS:

1. A data processing method comprising:
a reception step of receiving a request for data
loading from a terminal;
5 an end discrimination step of discriminating
whether the generation of requested data has ended;
a first transmission step of transmitting the
requested data if the generation thereof has ended;
an estimation step of estimating an end time if
10 the generation of the requested data has not ended; and
a second transmission step of transmitting the
estimated end time together with display information
indicating that the data generation is in progress.
- 15 2. A data processing method according to claim 1,
wherein said estimation step estimates the end time
based on the size of the generated data.
- 20 3. A data processing method according to claim 1,
wherein said data are result of execution of a
predetermined process, and said estimation step
estimates the end time based on the time required for
executing said predetermined process.
- 25 4. A data processing method comprising:
an issuing step of issuing a request for data
loading to a server;

a display step of displaying display data received
in response to said request; and

a re-issuing step, in case an estimated end time
for data generation is received together with said
5 display data, of issuing again the request for data
loading when said end time is reached.

5. A data processing apparatus comprising:

reception means for receiving a request for data
10 loading from a terminal;

end discrimination means for discriminating
whether the generation of requested data has ended;

first transmission means for transmitting the
requested data if the generation thereof has ended;

15 estimation means for estimating an end time if the
generation of the requested data has not ended; and

second transmission means for transmitting the
estimated end time together with display information
indicating that the data generation is in progress.

20

6. A data processing apparatus according to claim
5, wherein said estimation means estimates the end time
based on the size of the generated data.

25 7. A data processing apparatus according to claim
5, wherein said data are result of execution of a
predetermined process, and said estimation means

045697 120799

estimates the end time based on the time required for
executing said predetermined process.

8. A data processing apparatus comprising:

5 issuing means for issuing a request for data
loading to a server;

display means for displaying display data received
in response to said request; and

10 control means adapted, in case an estimated end
time for data generation is received together with said
display data, to so control said issuing means as to
issue again the request for data loading when said end
time is reached.

15 9. A computer readable storage medium storing a
data processing program for controlling a computer to
perform data processing, said program comprising codes
for causing the computer to perform:

20 a reception step of receiving a request for data
loading from a terminal;

an end discrimination step of discriminating
whether the generation of requested data has ended;

a first transmission step of transmitting the
requested data if the generation thereof has ended;

25 an estimation step of estimating an end time if
the generation of the requested data has not ended; and

a second transmission step of transmitting the

0945697 120799

estimated end time together with display information indicating that the data generation is in progress.

10. A computer readable storage medium storing a
5 data processing program for controlling a computer to perform data processing, said program comprising codes for causing the computer to perform:

an issuing step of issuing a request for data loading to a server;

10 a display step of displaying display data received in response to said request; and

a re-issuing step, in case an estimated end time for data generation is received together with said display data, of issuing again the request for data
15 loading when said end time is reached.

552021 6595460

ABSTRACT OF THE DISCLOSURE

In a navigation system in which the page data loaded from a server are displayed in a terminal, the server receiving the request for data loading from the terminal transmits the requested data if the data generation has ended, but, if not, estimates the end time and transmits the estimated end time together with display information indicating that the data generation is in progress. The terminal, issuing the request for data loading, displays the display data received in response to the request, and, if the estimated end time of data generation is received together with the display data, issues the request for data loading again when the estimated end time is reached. Thus efficient processing can be realized without wasted waiting time or wasted request for data loading in the terminal, in case the data generation requires a long time.

0945597 120799
962027 1659460



FIG. 1*FIG. 2*

FIG. 3




FIG. 4






FIG. 5



**FIG. 6A
PRIOR ART**



**FIG. 6B
PRIOR ART**




FIG. 7




FIG. 8





FIG. 9

**COMBINED DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION
(Page 1)**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled NAVIGATION APPARATUS CAPABLE OF GENERATING AND DISPLAYING INFORMATION AND METHOD THEREFOR, the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b), of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designates at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>(Yes/No) Priority Claimed</u>
JAPAN	10-368478	DECEMBER 10, 1998	YES

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 C.F.R. § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>Application No.</u>	<u>Filed (Day/Mo./Yr.)</u>	<u>Status (Patented, Pending, Abandoned)</u>
------------------------	----------------------------	--

I hereby appoint the practitioners associated with the firm and Customer Number provided below to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and direct that all correspondence be addressed to the address associated with that Customer Number:

FITZPATRICK, CELLA, HARPER & SCINTO
Customer Number: 05514

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole or First Inventor TSUNEHIRO TSUKADA

Inventor's signature _____

Date _____ Citizen/Subject of JAPAN

Residence 1210-2-503, TOKA ICHIBA-CHO, MIDORI-KU, YOKOHAMA-SHI,
KANAGAWA-KEN, JAPAN